



UV 镜头 NV7838UV (分辨率 100 lp/mm 焦距 78mm)



总览

UV 镜头系列 (分辨率 65 或 100 lp/mm)

通用参数

No.	名称(Name)	规格(Specification)	No.	名称(Name)	规格(Specification)
1	型号(Model)	NV7838UV	14	视场角 F.O.V(DxV xH)	"
2	物料代码(Material Code)	-			D
3	靶面格式(Image Format)	1"			H
4	分辨率(Resolution)	100 lp/mm			V
5	焦距(Focal Length)	78mm	15	接口(Mount)	C



	I Length)					
6	后截距(Back Focus)	65.02mm	16	适用物距 (Suitable Distance)	0.4m~ ∞ m	
7	F 值(F/No.)	3.8	17	z 佳物距 (Optimum Working Distance)	440mm-1500mm	
8	光圈(Iris Type)	Manual	18	镀膜(Coating)	200-1000nm	
9	畸变(Distortion)	<-0.05%	19	外形尺寸(Dimension)	$\Phi 52 \times 104.84$ mm	
10	通光口径 (Lens Effective Diameter)	前面(Front)	$\Phi 23.67$ mm	20	重量(Weight)	/
		后面(Back)	$\Phi 18.09$ mm	21	工作温度 (Operating Temperature)	-20~+65°C
11	相对照度 (Relative Illumination)	87.64%	22	镜头组成 (Lens Construction)	6-6	
12	光学总长(TL)	131.74mm	23	Max. 主光线入射角 (CRA)	5.07°	
13	设计波长 (Design Wavelength)	200-300nm	24	滤镜尺寸 (Filter Thread)	M30.5×0.5	

